

SPECIFICATIONS

| | |
|--------------------------------|----------------------------------------------------------------------------|
| STYLE NAME | Flex Fit II |
| CONSTRUCTION | Solid Vinyl Plank – Loose Lay |
| DIMENSIONS | 7.48" Wide x 48.19" Long |
| CLASS | (ASTM F1700/3261) Passes |
| • SIZE/SQUARENESS | (ASTM F2055) +/- 0.016 in per linear foot in size/<0.010 in for squareness |
| • DIMENSIONAL STABILITY | (ASTM F2199) < 0.020 in per linear foot |
| • RESIDUAL INDENTATION | (ASTM 1914) < 8% |
| • FLEXIBILITY | (ASTM F137) Passes 3" Mandrel, <1.0 in diameter, no cracks or breaks |
| • CHEMICAL RESISTANCE | (ASTM F925) Nothing more than slight |
| • HEAT RESISTANCE | (ASTM F1514) < 8.0 Δ E |
| • LIGHT RESISTANCE | (ASTM F1515) < 8.0 Δ E |
| WEAR LAYER THICKNESS | 20 Mil |
| OVERALL THICKNESS | 5 mm |
| BACKING CLASS | Commercial Grade |
| FINISH | Polyguard/hp (Polyurethane) |
| IIC RATING | (ASTM E492-09) > 53 when tested over 6" concrete with ceiling plenum |
| STATIC LOAD | (ASTM F970) < 0.005 at 500 psi, >750 or above |
| RADIANT PANEL | (ASTM 648) Class I |
| SMOKE DENSITY FLAMING | (ASTM 662) < 450 |
| SLIP RESISTANCE | (ASTM D2047) > 0.65 |
| WARRANTY | 15 Year Limited Commercial Wear Warranty |
| EDGE PROFILE | Micro Beveled Edge |
| INSTALLATION | Perimeter Glue/Floating |
| RECOMMENDED ADHESIVE | EverStep Evertite Transitional Adhesive |
| ANTIMICROBIAL TREATMENT | Yes |
| CASTER CHAIR | (ISO4918) Exceeds 5000 Cycles No Effect |
| RESISTANCE TO FUNGI | (ASTM G21) 0: Fungi Free |
| ANTIBACTERIAL ACTIVITY | Resists Bacterial Growth |