

SPECIFICATIONS

STYLE NAME	WARRIOR
CONSTRUCTION	Solid Vinyl Plank – Click Lock
DIMENSIONS	7" Wide x 48" Long
CLASS	(ASTM F1700/3261) Passes
<ul style="list-style-type: none">● SIZE/SQUARENESS● DIMENSIONAL STABILITY● RESIDUAL INDENTATION● FLEXIBILITY● CHEMICAL RESISTANCE● HEAT RESISTANCE● LIGHT RESISTANCE	(ASTM F2055) +/- 0.016 in per linear foot in size/<0.010 in for squareness (ASTM F2199) < 0.020 in per linear foot (ASTM 1914) < 8% (ASTM F137) Passes 3" Mandrel, <1.0 in diameter, no cracks or breaks (ASTM F925) Nothing more than slight (ASTM F1514) < 8.0 Δ E (ASTM F1515) < 8.0 Δ E
WEAR LAYER THICKNESS	12 Mil
OVERALL THICKNESS	4.5 mm (with 1mm IXPE Attached)
BACKING CLASS	Commercial Grade
FINISH	Polyguard/hp (Polyurethane)
IIC RATING	(ASTM E492-09) > 56 when tested over 6" concrete with ceiling plenum
STATIC LOAD	(ASTM F970) < 0.005 at 500 psi, >750 or above
RADIANT PANEL	(ASTM 648) Class I
SMOKE DENSITY FLAMING	(ASTM 662) < 450
SLIP RESISTANCE	(ASTM D2047) > 0.65
WARRANTY	10 Year Limited Commercial Wear Warranty
EDGE PROFILE	Micro Beveled Edge
INSTALLATION	Floating/Click Lock
ANTIMICROBIAL TREATMENT	Yes
CASTER CHAIR	(ISO4918) Exceeds 5000 Cycles No Effect
RESISTANCE TO FUNGI	(ASTM G21) 0: Fungi Free
ANTIBACTERIAL ACTIVITY	Resists Bacterial Growth
SCRATCH RESISTANCE COATING	EVERSHIELD