



EVERSTEP
LUXURY VINYL PLANK

DAVID MARTIN
VP Sales

c 423 596 7040
o 844 296 4669
e david.martin@everstepflooring.com
a 200 Emery West, Suite 3, Dalton, GA 30720
w everstepflooring.com

 floors for hospitality & contract
EVERSTEP
PRODUCT GUIDE



FLOORSCORE CERTIFICATION

FloorScore® is the most recognized indoor air quality (IAQ) certification standard for hard surface flooring materials, adhesives, and underlayments. Developed by SCS with the Resilient Floor Covering Institute (RFCI), a leading industry trade association of flooring manufacturers and suppliers, it qualifies for many green building schemes including LEED v4, WELL, BREEAM, and CHPS.

To learn more visit <https://www.scsglobalservices.com/services/floorscore>

DESIGN TOOLS & SAMPLES

EverStep provides the tools needed to work with demanding clients when specifying LVT. Our one-of-a-kind presentation system puts easy to use samples with clear information in your hands and our custom program gives you the flexibility to design with endless possibilities. Full planks and 9" samples are also available upon request.



EVERTITE ADHESIVE

No glue-down project is complete without EverTite Adhesive. Specially formulated to glue cork-backed or unbacked LVT to a variety of substrates, EverTite is the easiest way to ensure a successful installation. Available in handy 4 gallon pails.

EVERPRIME PRIMER

Every successful installation begins with proper preparation, and there's no better place to start than with EverPrime floor primer. For a few cents per square foot, EverPrime encapsulates loose particulates, providing a more stable and consistent level of adhesion.



EVERCUSH UNDERLAYMENT

For additional noise reduction and cushion underfoot, there's no better solution than EverCush underlayment. EverCush can be installed under click-lock or glue-down LVT for increased performance and longer product life.

CLOUD NINE PRO II



CNP8353-14
WHISKEY



CNP8370-10
WINTER TAUPE



CNP-256-5
MOUNTAIN ASH



CNP8295-10
BARN DOOR



CNP-6151-6
CASTLE GRAY



CNP9002-04
WEATHERED TEAK

Cloud Nine Pro II is a waterproof, SPC, click-lock luxury vinyl tile with a IXPE backing for additional noise reduction and comfort underfoot. It has a 20-mil wear layer and Evershield protective UV scratch resistant coating. Cloud Nine Pro II is the most durable option available for hospitality, multi-family, and commercial projects and boasts a 25 year commercial warranty.

CONSTRUCTION

Luxury Vinyl Tile Click Lock

DIMENSIONS

7.24" Wide x 48" Long

CLASS

(ASTM F1700/3261) Passes

- SIZE/SQUARENESS (ASTM F2055) +/- 0.016 in per linear foot in size <0.010 in for squareness
- DIMENSIONAL STABILITY (ASTM F2199) < 0.020 in per linear foot
- RESIDUAL INDENTATION (ASTM 1914) < 10%
- FLEXIBILITY (ASTM F137) Passes 3" Mandrel, <1.0 in diameter, no cracks or breaks
- CHEMICAL RESISTANCE (ASTM F925) Nothing more than slight
- HEAT RESISTANCE (ASTM F1514) < 8.0 Δ E
- LIGHT RESISTANCE (ASTM F1515) < 8.0 Δ E

WEAR LAYER THICKNESS

20 Mil

OVERALL THICKNESS

6.5 mm

BACKING CLASS

Commercial Grade

FINISH

Polyguard/hp (Polyurethane)

IIC RATING

(ASTM E492-09) > 62 when tested over 6" concrete with ceiling plenum

STATIC LOAD

(ASTM F970) < 0.005 at 500 psi, >750 or above

RADIANT PANEL

(ASTM 648) Class I

SMOKE DENSITY FLAMING

(ASTM 662) < 450

SLIP RESISTANCE

(ASTM D2047) > 0.65

WARRANTY

25 Year Limited Commercial Wear Warranty

EDGE PROFILE

Micro Beveled Edge

INSTALLATION

Click Lock

RECOMMENDED ADHESIVE

N/A

ANTIMICROBIAL TREATMENT

Yes

CASTER CHAIR

(ISO4918) Exceeds 5000 Cycles No Effect

RESISTANCE TO FUNGI

(ASTM G21) 0: Fungi Free

ANTIBACTERIAL ACTIVITY

Resists Bacterial Growth

ATTACHED PADDING

1.5mm IXPE



HERCULES PRO



Hercules Pro is a waterproof glue-down luxury vinyl tile with a 1.5mm cork backing for additional noise reduction and comfort underfoot. It has a 30-mil wear layer and Evershield protective UV scratch resistant coating. Hercules Pro is a durable, budget-friendly option for hospitality, multi-family, senior living, and restaurants.

CONSTRUCTION

Luxury Vinyl Tile Glue Down

DIMENSIONS

6.1" Wide x 48.4" Long

CLASS

(ASTM F1700/3261) Passes

- SIZE/SQUARENESS (ASTM F2055) +/- 0.016 in per linear foot in size
<0.010 in for squareness
- DIMENSIONAL STABILITY (ASTM F2199) < 0.020 in per linear foot
- RESIDUAL INDENTATION (ASTM 1914) < 10%
- FLEXIBILITY (ASTM F137) Passes 3" Mandrel,
<1.0 in diameter, no cracks or breaks
- CHEMICAL RESISTANCE (ASTM F925) Nothing more than slight
- HEAT RESISTANCE (ASTM F1514) < 8.0 Δ E
- LIGHT RESISTANCE (ASTM F1515) < 8.0 Δ E

WEAR LAYER THICKNESS

30 Mil

OVERALL THICKNESS

4.5 mm

BACKING CLASS

Commercial Grade

FINISH

Polyguard/hp (Polyurethane)

IIC RATING

**(ASTM E492-09) > 64 when tested over
6" concrete with ceiling plenum**

STATIC LOAD

(ASTM F970) < 0.005 at 500 psi, >750 or above

RADIANT PANEL

(ASTM 648) Class I

SMOKE DENSITY FLAMING

(ASTM 662) < 450

SLIP RESISTANCE

(ASTM D2047) > 0.65

WARRANTY

20 Year Limited Commercial Wear Warranty

EDGE PROFILE

Micro Beveled Edge

INSTALLATION

Glue Down

RECOMMENDED ADHESIVE

Evertite Adhesive

ANTIMICROBIAL TREATMENT

Yes

CASTER CHAIR

(ISO4918) Exceeds 5000 Cycles No Effect

RESISTANCE TO FUNGI

(ASTM G21) 0: Fungi Free

ANTIBACTERIAL ACTIVITY

Resists Bacterial Growth

ATTACHED PADDING

1.5mm Attached IXPE



HER001-12
ASH



HER001-01
SIENNA



HER8353-06
RIVERWOOD



HER6151-06
CASTLE GRAY



HER5411-02
INDIAN SUMMER



HER113-14
HARBOR GRAY



HER-8504-10
FRENCH ROAST



HER022-02
GUNSTOCK



DURA CHOICE III



Dura Choice III is a waterproof, SPC, click-lock luxury vinyl tile that is perfect for any renovation. It has a 20-mil wear layer and Evershield protective UV scratch resistant coating. Dura Choice III is a durable, option for hospitality, multi-family, and commercial projects..

CONSTRUCTION

Luxury Vinyl Tile Click Lock

DIMENSIONS

7.24" Wide x 48" Long

CLASS

(ASTM F1700/3261) Passes

- SIZE/SQUARENESS (ASTM F2055) +/- 0.016 in per linear foot in size
<0.010 in for squareness
- DIMENSIONAL STABILITY (ASTM F2199) < 0.020 in per linear foot
- RESIDUAL INDENTATION (ASTM 1914) < 10%
- FLEXIBILITY (ASTM F137) Passes 3" Mandrel,
<1.0 in diameter, no cracks or breaks
- CHEMICAL RESISTANCE (ASTM F925) Nothing more than slight
- HEAT RESISTANCE (ASTM F1514) < 8.0 Δ E
- LIGHT RESISTANCE (ASTM F1515) < 8.0 Δ E

WEAR LAYER THICKNESS

20 Mil

OVERALL THICKNESS

5 mm

BACKING CLASS

Commercial Grade

FINISH

Polyguard/hp (Polyurethane)

IIC RATING

**(ASTM E492-09) > 60 when tested over
6" concrete with ceiling plenum**

STATIC LOAD

(ASTM F970) < 0.005 at 500 psi, >750 or above

RADIANT PANEL

(ASTM 648) Class I

SMOKE DENSITY FLAMING

(ASTM 662) < 450

SLIP RESISTANCE

(ASTM D2047) > 0.65

WARRANTY

15 Year Limited Commercial Wear Warranty

EDGE PROFILE

Micro Beveled Edge

INSTALLATION

Click Lock

RECOMMENDED ADHESIVE

N/A

ANTIMICROBIAL TREATMENT

Yes

CASTER CHAIR

(ISO4918) Exceeds 5000 Cycles No Effect

RESISTANCE TO FUNGI

(ASTM G21) 0: Fungi Free

ANTIBACTERIAL ACTIVITY

Resists Bacterial Growth

ATTACHED PADDING

1mm IXPE



DC133-16
LINEN



DC508-07
PEBBLE



DC611L-07
MOONBEAM



DC718L-01
WINE BARREL



DC792-07
OLD PENNY



DC802B-08
CONCRETE



DC6151-06
CASTLE GRAY



DC9002-04
WEATHERED TEAK



DC-020-11
BEIGE SHADOW



DC-016-10
OSPREY OAK

FLEX FIT II



Flex Fit II is easy to install Loose lay and a damaged plank can be easily replaced and replacement planks can be stored in a closet. It pairs great with carpet tiles and eliminates the need for transition strips. 7"x 48" planks make the installation fast. 5mm with a 20 Mil wear layer, loose lay, 100% waterproof, 15-year commercial warranty.

CONSTRUCTION

Solid Vinyl Plank – Loose Lay

DIMENSIONS

7.48" Wide x 48.19" Long

CLASS

(ASTM F1700/3261) Passes

• SIZE/SQUARENESS

(ASTM F2055) +/- 0.016 in per linear foot in size/<0.010 in for squareness

• DIMENSIONAL STABILITY

(ASTM F2199) < 0.020 in per linear foot

• RESIDUAL INDENTATION

(ASTM 1914) < 8%

• FLEXIBILITY

(ASTM F137) Passes 3" Mandrel, <1.0 in diameter, no cracks or breaks

• CHEMICAL RESISTANCE

(ASTM F925) Nothing more than slight

• HEAT RESISTANCE

(ASTM F1514) < 8.0 Δ E

• LIGHT RESISTANCE

(ASTM F1515) < 8.0 Δ E

WEAR LAYER THICKNESS

20 Mil

OVERALL THICKNESS

5 mm

BACKING CLASS

Commercial Grade

FINISH

Polyguard/hp (Polyurethane)

IIC RATING

(ASTM E492-09) > 58 when tested over 6" concrete with ceiling plenum

STATIC LOAD

(ASTM F970) < 0.005 at 500 psi, >750 or above

RADIANT PANEL

(ASTM 648) Class I

SMOKE DENSITY FLAMING

(ASTM 662) < 450

SLIP RESISTANCE

(ASTM D2047) > 0.65

WARRANTY

15 Year Limited Commercial Wear Warranty

EDGE PROFILE

Micro Beveled Edge

INSTALLATION

Perimeter Glue/Floating

RECOMMENDED ADHESIVE

EverStep Evertite Transitional Adhesive

ANTIMICROBIAL TREATMENT

Yes

CASTER CHAIR

(ISO4918) Exceeds 5000 Cycles No Effect

RESISTANCE TO FUNGI

(ASTM G21) 0: Fungi Free

ANTIBACTERIAL ACTIVITY

Resists Bacterial Growth



Bazillian Oak



Charleston



Coast



Mystic



Phoenix



Winterwood

MASTER FLEX

Master Flex is a 100% waterproof, 8mm, click lock luxury vinyl tile that is perfect for any project. It is a 20 mil wear layer with a Evershield Scratch Resistance Coating. Master Flex is a very durable, option for any hospitality installation in the rooms or public space areas.



AM9501-1
Cappuccino



AM9502-4
Rustic Oak



CBD190L-14
Timeless Ash



AM9502-6
Antique Ash



CDW302L-08
Pine Blossom



KBW1084L-2
Carbon



AM9501-3
Limed Oak



CD302L-09
Homestead



CDB190L-12
White Timber

STYLE NAME	Master Flex
CONSTRUCTION	Solid Vinyl Plank – Click Lock
DIMENSIONS	7" Wide x 60" Long
CLASS	(ASTM F1700/3261) Passes
• SIZE/SQUARENESS	(ASTM F2055) +/- 0.016 in per linear foot in size/<0.010 in for squareness
• DIMENSIONAL STABILITY	(ASTM F2199) < 0.020 in per linear foot
• RESIDUAL INDENTATION	(ASTM 1914) < 8%
• FLEXIBILITY	(ASTM F137) Passes 3" Mandrel, <1.0 in diameter, no cracks or breaks
• CHEMICAL RESISTANCE	(ASTM F925) Nothing more than slight
• HEAT RESISTANCE	(ASTM F1514) < 8.0 Δ E
• LIGHT RESISTANCE	(ASTM F1515) < 8.0 Δ E
WEAR LAYER THICKNESS	20 Mil
OVERALL THICKNESS	8.0 mm
BACKING CLASS	Commercial Grade
FINISH	Polyguard/hp (Polyurethane)
IIC RATING	(ASTM E492-09) > 65 when tested over 6" concrete with ceiling plenum
STATIC LOAD	(ASTM F970) < 0.005 at 500 psi, >750 or above
RADIANT PANEL	(ASTM 648) Class I
SMOKE DENSITY FLAMING	(ASTM 662) < 450
SLIP RESISTANCE	(ASTM D2047) > 0.65
WARRANTY	15 Year Limited Commercial Wear Warranty
EDGE PROFILE	Micro Beveled Edge
INSTALLATION	Floating/Click Lock
ANTIMICROBIAL TREATMENT	Yes
CASTER CHAIR	(ISO4918) Exceeds 5000 Cycles No Effect
RESISTANCE TO FUNGI	(ASTM G21) 0: Fungi Free
ANTIBACTERIAL ACTIVITY	Resists Bacterial Growth
SCRATCH RESISTANCE COATING	EVERSHIELD
ATTACHED PADDING	1.5mm Attached Eva Padding For Sound Abatement

SPECIALS 101

Specials 101 is a waterproof, click lock luxury vinyl tile that is perfect for any budget-driven renovation. It has a Evershield protective UV scratch resistant coating. Specials 101 is a 5mm with a attached 1mm attached IXPE padding, with a 20 Mil wear layer.

CONSTRUCTION

DIMENSIONS

CLASS

• SIZE/SQUARENESS

• DIMENSIONAL STABILITY

• RESIDUAL INDENTATION

• FLEXIBILITY

• CHEMICAL RESISTANCE

• HEAT RESISTANCE

• LIGHT RESISTANCE

WEAR LAYER THICKNESS

OVERALL THICKNESS

BACKING CLASS

FINISH

IIC RATING

STATIC LOAD

RADIANT PANEL

SMOKE DENSITY FLAMING

SLIP RESISTANCE

WARRANTY

EDGE PROFILE

INSTALLATION

ANTIMICROBIAL TREATMENT

CASTER CHAIR

RESISTANCE TO FUNGI

ANTIBACTERIAL ACTIVITY

SCRATCH RESISTANCE COATING

ATTACHED PADDING

Luxury Vinyl Tile Click Lock

7" Wide x 48" Long

(ASTM F1700/3261) Passes

(ASTM F2055) +/- 0.016 in per

linear foot in size

<0.010 in for squareness

(ASTM F2199) < 0.020 in per linear foot

(ASTM 1914) < 10%

(ASTM F137) Passes 3" Mandrel,

<1.0 in diameter, no cracks or breaks

(ASTM F925) Nothing more than slight

(ASTM F1514) < 8.0 Δ E

(ASTM F1515) < 8.0 Δ E

20 Mil

5 mm

Commercial Grade

Polyguard/hp (Polyurethane)

(ASTM E492-09) > 56 when tested over

6" concrete with ceiling plenum

(ASTM F970) < 0.005 at 500 psi,

>750 or above

(ASTM 648) Class I

(ASTM 662) < 450

(ASTM D2047) > 0.65

15 Year Limited Commercial Wear Warranty

Micro Beveled Edge

Floating/Click Lock

Yes

(ISO4918) Exceeds 5000 Cycles No Effect

(ASTM G21) 0: Fungi Free

Resists Bacterial Growth

EVERSHIELD

1mm IXPE



AM1027-3



AM1510-7



AM9501-1

