SPECIFICATIONS

STYLE NAME	**Bayfront**
CONSTRUCTION	Loose Lay- ERT Enhanced Resilient Tile
DIMENSIONS	**9**" Wide x 48" Long
CLASS	(ASTM F1700/3261) Passes
• **SIZE/SQUARENESS**	(ASTM F2055) +/- 0.016 in per linear foot in size/<0.010 in for squareness
• **DIMENSIONAL STABILITY**	(ASTM F2199) < 0.020 in per linear foot
• **RESIDUAL INDENTATION**	(ASTM 1914) < 8%
• **FLEXIBILITY**	(ASTM F137) Passes 3" Mandrel, <1.0 in diameter, no cracks or breaks
• **CHEMICAL RESISTANCE**	(ASTM F925) Nothing more than slight
• **HEAT RESISTANCE**	(ASTM F1514) < 8.0 Δ E
• **LIGHT RESISTANCE**	(ASTM F1515) < 8.0 Δ E
WEAR LAYER THICKNESS	20 Mil
OVERALL THICKNESS	5 mm
BACKING CLASS	Commercial Grade
FINISH	Polyguard/hp (Polyurethane)
IIC RATING	(ASTM E492-09) > 60 when tested over 6" concrete with ceiling plenum
STATIC LOAD	(ASTM F970) < 0.005 at 500 psi, >750 or above
RADIANT PANEL	(ASTM 648) Class I
SMOKE DENSITY FLAMING	(ASTM 662) < 450
SLIP RESISTANCE	(ASTM D2047) > 0.65
WARRANTY	15 Year Limited Commercial Wear Warranty
EDGE PROFILE	Micro Beveled Edge
INSTALLATION	Perimeter Glue/Floating
RECOMMENDED ADHESIVE	EverStep Evertite Transitional Adhesive
ANTIMICROBIAL TREATMENT	Yes
CASTER CHAIR	(ISO4918) Exceeds 5000 Cycles No Effect
RESISTANCE TO FUNGI	(ASTM G21) 0: Fungi Free
ANTIBACTERIAL ACTIVITY	Resists Bacterial Growth

floors for hospitality
EVERSTEP

floor score
CERTIFIED BY SCS Global Services